



Type Mark	Count	Description	Frame Finish	Door Leaf Finish	Ironmongery Type
D14	1	D14 - Rovere Valdweg Aleve woodgrain laminate faced, semi-solid timber, Double door with hardwood edgings and GMS frame to painted finish. Size and configuration: As shown on the Project Door Schedule. Fire rating: Class B to SANS 1253. Stability: 120 min integrity and insulation 60 min. Intumescent fire seals to suit fire ratings. Doors to be labelled, indicating manufacturers name, reference no. and year of manufacture. FRAME: 1.6mm GMS Pressed stressed frame to receive paint finish, wall thickness as indicated on plan. LEAF: semi-solid timber, flush panel, double doors with hardwood edgings all round. Facing: 0.7mm Rovere Valdweg Aleve woodgrain laminate. Edges: 25mm Concealed hardwood edge. Thickness: 44mm.	Primed and painted to match RAL 7043	Rovere Valdweg Aleve woodgrain laminate	Refer to ironmongery schedule

GENERAL NOTES		Rev	Date	Int	Description
<ul style="list-style-type: none"> - All installation procedures to comply with good building practice and deemed to satisfy the Architect's requirements. -All exposed timber to be rubbed down smooth prior the application of any finish. -To be supplied and installed with all door frames. -This drawing to be read in conjunction with GA-layouts and all dimensions to be checked on site. -Refer any discrepancies to the Architect in writing. 		A	2024-11-11		For Tender
		B	2024-11-25		For Tender

Title.	Drawing No.	Scale	Date	Rev.
Door Type D14	SMFN-SVA-AR-SH-30_1015	1 : 25	2020/09/02	B