



Type Mark	Count	Description	Frame Finish	Door Leaf Finish	Ironmongery Type
D5	1	D5 - Solid core timber, double door with GMS frame to painted finish. Size and configuration: As shown on the Project Door Schedule. Fire rating: Class B to SANS 1253. Stability: 120 min integrity and insulation 60 min. Intumescent fire seals to suit fire ratings. Doors to be labelled, indicating manufacturers name, fire rating, reference no. and year of manufacture. FRAME: 1.6mm GMS frame designed to achieve requisite fire rating, and wall thickness as indicated on plan. LEAF: Solid core timber, flush panel, double door. Facing: Door to receive painted as per paint schedule.	Primed and painted to match RAL 7043	Primed and painted as per paint schedule	Refer to ironmongery schedule

GENERAL NOTES		Rev	Date	Int	Description
<ul style="list-style-type: none"> - All installation procedures to comply with good building practice and deemed to satisfy the Architect's requirements. -All exposed timber to be rubbed down smooth prior the application of any finish. -To be supplied and installed with all door frames. -This drawing to be read in conjunction with GA-layouts and all dimensions to be checked on site. -Refer any discrepancies to the Architect in writing. 		A	2024-11-25		For Tender

Title.

Door Type D5

Drawing No.

SMFN-SVA-AR-30_1005

Scale

1 : 25

Date

11/18/24

Rev.

A