



Type Mark	Count	Description	Frame Finish	Door Leaf Finish	Ironmongery Type
D15	1	D15 - Solid core timber, single door with GMS frame to painted finish. Size and configuration: As shown on the Project Door Schedule. Fire rating: Non-rated. Doors to be labelled, indicating manufacturers name, fire rating, reference no. and year of manufacture. FRAME: 1.6mm GMS frame designed to achieve requisite fire rating, and wall thickness as indicated on plan. LEAF: solid core timber, flush panel, single door to receive paint finish.	Primed and painted to match RAL 7043	Primed and painted as per paint schedule	Refer to ironmongery schedule

GENERAL NOTES		Rev	Date	Int	Description
<ul style="list-style-type: none"> - All installation procedures to comply with good building practice and deemed to satisfy the Architect's requirements. -All exposed timber to be rubbed down smooth prior the application of any finish. -To be supplied and installed with all door frames. -This drawing to be read in conjunction with GA-layouts and all dimensions to be checked on site. -Refer any discrepancies to the Architect in writing. 		A	2024-11-11		For Tender
		B	2024-11-25		For Tender
		C	2024-12-03		For Tender

Title.	Drawing No.	Scale	Date	Rev.
Door Type D15	SMFN-SVA-AR-30_1016	1 : 25	2020/09/02	C