



Type Mark	Count	Description	Frame Finish	Door Leaf Finish	Ironmongery Type
D1	10	D1-Rovere Valdweg Aleve woodgrain laminate faced, semi-solid timber, single door with hardwood edgings all round. Size and configuration: As shown on the Project Door Schedule. SANS 545 classification: Performance: Heavy duty. Exposure: Internal. Fire rating: Non-rated. Configuration: Single leaf, single swing. Doors to be delivered with protection for the finished surfaces. FRAME: 44x69mm solid Light Oak frame to receive oil finish with 45x15mm rebates per detail drawings. Size: As shown on the Contract Drawings and the Project Door Schedule. LEAF: semi-solid timber, flush panel, single door with hardwood edges all round. Facing: 0.7mm Rovere Valdweg Aleve woodgrain laminate. Edges: 25mm concealed hardwood edges all round. Thickness: 44mm.	Jax-Oleum oil finish - Corn Silk	Rovere Valdweg Aleve woodgrain laminate	Refer to ironmongery schedule

GENERAL NOTES		Rev	Date	Int	Description
- All installation procedures to comply with good building practice and deemed to satisfy the Architect's requirements. -All exposed timber to be rubbed down smooth prior the application of any finish. -To be supplied and installed with all door frames. -This drawing to be read in conjunction with GA-layouts and all dimensions to be checked on site. -Refer any discrepancies to the Architect in writing.		A	2024-11-11		For Tender
		B	2024-11-25		For Tender
		C	2024-12-06		For Tender

Title.	Drawing No.	Scale	Date	Rev.
Door Type D1	SMFN-SVA-AR-30_1001	1 : 25	2020/09/02	C