



Type Mark	Count	Description	Frame Finish	Door Leaf Finish	Ironmongery Type
D9	3	D9- Rovere Valdweg Aleve woodgrain laminate faced, semi solid timber, single door with hardwood edgings and GMS frame to receive painted finish. Size and configuration: As shown on the Project Door Schedule. SANS 545 classification: Performance: Heavy duty. Exposure: Internal. Fire rating: Class B to SANS 1253. Stability: 120 min integrity and insulation 60 min. Intumescent fire seals to suit fire ratings. Doors to be labelled, indicating manufacturers name, fire rating, reference no. and year of manufacture. FRAME: 1.6mm GMS Pressed stressed frame designed to achieve requisite fire rating, and wall thickness as indicated on plan To receive painted finish. LEAF: Semi-solid timber, flush panel, single door with hardwood edgings all round. Facing: 0.7mm Rovere Valdweg Aleve woodgrain laminate. Edges: 25mm Concealed hardwood edge.	Primed and painted to match RAL 7043	Rovere Valdweg Aleve woodgrain laminate	Refer to ironmongery schedule

GENERAL NOTES		Rev	Date	Int	Description
- All installation procedures to comply with good building practice and deemed to satisfy the Architect's requirements. -All exposed timber to be rubbed down smooth prior the application of any finish. -To be supplied and installed with all door frames. -This drawing to be read in conjunction with GA-layouts and all dimensions to be checked on site. -Refer any discrepancies to the Architect in writing.		A	2024-11-11		For Tender
		B	2024-11-25		For Tender
		C	2024-12-03		For Tender

Title.	Drawing No.	Scale	Date	Rev.
<b>Door Type D9</b>	<b>SMFN-SVA-AR-SH-30_1009</b>	1 : 25	2020/09/02	C