



Type Mark	Count	Description	Frame Finish	Door Leaf Finish	Ironmongery Type
D6	1	D6-Rovere Valdweg Aleve woodgrain laminate faced, semi solid timber, single door with hardwood edgings. Frame to accommodate full height fixed side glass panel. Size and configuration as shown on the Project Door Schedule. SANS 545 classification: Performance: Heavy duty. Exposure: Internal. Fire rating: Non-rated. Acoustic rating: Non-rated. Configuration: Single Leaf, single swing. Doors to be delivered with protection for the finished surfaces. FRAME: 44x69mm solid Light Oak frame to receive oil finish with 45x15mm rebates per detail drawings. Size: As shown on the Contract Drawings and the Project Door Schedule. LEAF: semi-solid timber, flush panel, single door with hardwood edgings all round. Facing: 0.7mm Rovere Valdweg Aleve woodgrain laminate to clad all faces of door leaf and frame. Edges: 25mm Concealed hardwood edge. Thickness: 44mm.	Jax-Oleum oil finish - Corn Silk	Rovere Valdweg Aleve woodgrain laminate	

GENERAL NOTES		Rev	Date	Int	Description
<ul style="list-style-type: none"> - All installation procedures to comply with good building practice and deemed to satisfy the Architect's requirements. -All exposed timber to be rubbed down smooth prior the application of any finish. -To be supplied and installed with all door frames. -This drawing to be read in conjunction with GA-layouts and all dimensions to be checked on site. -Refer any discrepancies to the Architect in writing. 		A	2024-11-25		For Tender
		B	2024-11-28		For Tender

Title.	Drawing No.	Scale	Date	Rev.
Door Type D6	SMFN-SVA-AR-30_1006	1 : 25	11/18/24	B