



PROJECT NAME: SANSА - Matjiesfontein

PROFESSIONAL: SVA Architects

CONSULTANT: Chantelle Pieters - 066 474 1884 - chantelle.pieters@ahzа.com

REVISION: v 3

REPORT DATE: 31/01/2025

**dormakaba** 

## Project Information

All aspects of this Door Hardware Schedule should be checked and confirmed with all the current documentation available for this project by the hardware distributor prior to the ordering of any hardware.

- For pricing of this door hardware schedule, please contact your regular architectural hardware distributor or contact **dormakaba** for a list of distributors in your area. Alternatively, product and pricing assistance can be obtained via [info.za@dormakaba.com](mailto:info.za@dormakaba.com)
- Door and frame details (including sizes) shown in this door hardware schedule are indicative only and only used as a guide to hardware requirements. All door and frame details should be confirmed from the Architect's most recent documentation.
- If **dormakaba** Automatic doors have been noted in this specification, the full specification, pricing and installation details should be confirmed and priced by **dormakaba**. Please contact your preferred dormakaba consultant for further information.
- All non **dormakaba** hardware specified in this door hardware schedule must be checked with the relevant manufacturer for suitability and availability by the hardware distributor prior to ordering of the hardware.
- The hardware distributor will need to confirm all handing of all products from the latest floor plans prior to the ordering of any hardware. This includes, but is not limited to, all handed locks, furniture, offset pivots, lift-off hinges, etc.
- Where the **dormakaba** ED Series are specified, the provision / installation of fire stopping products or material to penetrations is not allowed for under the **dormakaba** scope of works. This to be carried out by others.
- Panic Bars (where specified) will need to have final sizes confirmed with actual door widths and heights by the hardware distributor prior to ordering.
- Where surface mounted door closers have been scheduled, they should generally be installed to the less visible side of the door. The door closers scheduled require minimum nib room of 60mm when mounted to the pull side of the door.
- Where surface mounted door closers have been scheduled to aluminium or timber glazed doors, a larger top rail (nominal 110mm) should be specified to allow for secure mounting of the door closer. The hardware distributor is to confirm with the door supplier the need for a drop or trim plate.
- Where kickplates have been specified, the builder should organize and allow for the cost of providing final kickplate measurements to the hardware distributor prior to ordering.
- Where door seals have been specified, the hardware distributor will need to confirm the seal sizes and types are compatible with the actual door type, door widths and heights prior to ordering.
- Where seals have been specified to match acoustic requirements, the acoustic consultant is to confirm these seals are suitable to achieve the acoustic ratings required. The door hardware specified may need to be altered if different seals are used.
- Where seals have been specified to smoke doors, the fire / smoke door contractor is to confirm these seals are suitable to comply with the SABS requirements for this project. The door hardware specified may need to be altered if different seals are used.

## Project Information

- Where access control and security products have been scheduled, they are only indicatively specified in this door hardware schedule. For full details and specifications refer to the separate Access Control Quotation. The electronic products included in this door hardware schedule should be checked and coordinated with the information shown on the separate Access Control Quotation to ensure adequate power and cabling has been allowed for. The builder is to confirm that the electronic products included in this door hardware schedule are to be part of the hardware distributor's package.
- Refer to individual doors, hardware sets and products for notes that will need to be addressed.

### Abbreviations used, finishes and descriptions

CYL	Cylinder
MK	Master Keyed
GMK	Grand Master Keyed
KA	Keyed Alike
KD	Keyed to Differ
BT	Bolt Through
BTB	Back to Back
LH	Left Hand
RH	Right Hand
N/S	Narrow Stile
H/O	Hold Open
D/A	Delayed Action
DD	Double Door
SLD	Sliding Door
EAC	Electronic Access Control
PSS	Polished Stainless Steel
SSS	Satin Stainless Steel
SS	Stainless Steel
GAL	Galvanized
ZP	Zinc Plated
PB	Polished Brass
SB	Satin Brass
PCP	Polished and Chrome Plated
SCP	Satin Chrome Plated
PNP	Polished Nickel Plated
SNP	Satin Nickel Plated
PC	Powder Coated
EP	Electro-plating
PVD	Physical Vapor Disposition

### Colouring Legend

	Door / Product has been added to this revision.
	Door / Product has changed since the last revision.
	Door / Product has been removed from this revision.

# Control List

PROJECT NAME: SANSА - Matjiesfontein

REPORT DATE: 31/01/2025

PROFESSIONAL: SVA Architects

REVISION DATE: 31/01/2025

CONSULTANT: Chantelle Pieters - 066 474 1884 - chantelle.pieters@ahhza.com

REVISION: v 3

Door Number	Hardware Set	Area	Location	Door Type	Handing
3A.D9	T08	MAIN BLDG	SANSА EQUIP. ROOM	D9	RH
4A.D5	T07	MAIN BLDG	SANSА EQUIP. ROOM	D5	DD
5A.D9	T08	MAIN BLDG	SANSА EQUIP. ROOM	D9	LH
9A.D7	T07	MAIN BLDG	ELECTRONIC WKSHP	D7	DD
10A.D14	T07	MAIN BLDG	POWER DISTRIBUTION	D14	DD
11A.D7	T07	MAIN BLDG	EQUIP. STORE	D7	DD
12A.D4	T07	MAIN BLDG	NASА CONTROL	D4	FIRE DD
13A.D15	T08	MAIN BLDG	NASА CONTROL	D15	LH
14A.D11	T07	MAIN BLDG	NASА STORE	D11	DD
15A.D5	T07	MAIN BLDG	LOGISTICS	D5	DD
16A.D15	T08	MAIN BLDG	NASА STORE	D15	LH
17A.D3	T07	MAIN BLDG	LOGISTICS	D3	DD
20A.D6	T08	MAIN BLDG	CICULATION	D6	RH
21A.D10	T01	MAIN BLDG	OFFICE	D10	LH
22A.D10	T01	MAIN BLDG	OFFICE	D10	LH
23A.D10	T01	MAIN BLDG	OFFICE	D10	LH
24A.D10	T01	MAIN BLDG	OFFICE	D10	RH
25A.D1	T11	MAIN BLDG	ABLUTION	D1	LH
26A.D1	T11	MAIN BLDG	ABLUTION	D1	RH
27A.D1	T09	MAIN BLDG	OFFICE?	D1	RH
39A.D1	T01	MAIN BLDG	KITCHEN	D1	LH
40A.D16	T09	MAIN BLDG	STORE	D16	RH
43A.D10	T02	MAIN BLDG	MALE ABL.	D10	RH
44A.D17	T04	MAIN BLDG	WC	D17	LH
45A.D17	T04	MAIN BLDG	WC	D17	LH
45A.D10	T03	MAIN BLDG	FEMALE ABL.	D10	RH
46A.D17	T04	MAIN BLDG	WC	D17	LH
47A.D17	T04	MAIN BLDG	WC	D17	LH
48A.D17	T04	MAIN BLDG	WC	D17	LH
49A.D17	T04	MAIN BLDG	WC	D17	LH
50A.D17	T04	MAIN BLDG	WC	D17	LH
51A.D2	T06	MAIN BLDG	DISABLED	D2	LH
52A.D12	T12	MAIN BLDG	AUDITORIUM	D12	DD
54A.D8	T10	MAIN BLDG	AUDITORIUM	D8	LH
1B.D18	T06	GATEHOUSE	DISABLED	D18	RH
2B.D1	T04	GATEHOUSE	WC	D1	LH

# Control List

PROJECT NAME: SANSA - Matjiesfontein

REPORT DATE: 31/01/2025

PROFESSIONAL: SVA Architects

REVISION DATE: 31/01/2025

CONSULTANT: Chantelle Pieters - 066 474 1884 - chantelle.pieters@ahhza.com

REVISION: v 3

Door Number	Hardware Set	Area	Location	Door Type	Handing
3B.D1	T04	GATEHOUSE	WC	D1	LH
4B.D1	T04	GATEHOUSE	WC	D1	LH
5B.D1	T04	GATEHOUSE	WC	D1	LH
6B.D8	T08	GATEHOUSE	SECURITY CTRL	D8	LH
7B.D8	T01	GATEHOUSE	SAFE	D8	LH
11B.D16	T09	GATEHOUSE	SECURITY CTRL	D16	RH
1C.D10	T01	GENERATOR	OFFICE	D10	LH
2C.D10	T01	GENERATOR	OFFICE	D10	RH
4C.D1	T04	GENERATOR	WC	D1	RH
5C.D1	T04	GENERATOR	WC	D1	RH
6C.D2	T06	GENERATOR	DISABLED	D2	RH
7C.D18	T05	GENERATOR	SHOWER FACILITY	D18	LH
9C.D11	T07	GENERATOR	TRANSFORMER	D11	DD
10C.D11	T07	GENERATOR	M/LV PLANT	D11	DD
12C.D16	T08	GENERATOR	FLAMMABLE MATERIAL	D16	RH
13C.D16	T09	GENERATOR	USED OIL	D16	LH

# HARDWARE PER SET

PROJECT NAME: SANSA - Matjiesfontein

REPORT DATE: 31/01/2025

PROFESSIONAL: SVA Architects

REVISION DATE: 31/01/2025

CONSULTANT: Chantelle Pieters - 066 474 1884 - chantelle.pieters@ahhza.com

REVISION: v 3

Hardware for Set:		T01			
Hardware Set Quantity :		1			
Notes					
Doors (8)		21A.D10, 22A.D10, 23A.D10, 24A.D10, 39A.D1, 7B.D8, 1C.D10, 2C.D10			
Product Image	Product Code	Description	Finish	Qty	Units
	DBB-SS-009	dormakaba 102x75x3mm, EN1935 Grade 13, Two ball bearing butt hinge. Fire rated. 120kg Carrying capacity per pair. Finish: Stainless Steel	Stainless Steel	1.5	Pair
	TH125 Cyl S.S	dormakaba Lever handle on rose with Cylinder escutcheons	Stainless Steel	1	Set
	D036S SS	dormakaba Cylinder Sash Lock. Case dimensions (mm) 116.5H x 78D. Forend dimensions (mm) 168H x 22W. Backset 57mm. Centres 61mm.	Stainless Steel	1	Each
	DDC206301 GMK	dormakaba 63mm - 31.5+31.5mm Europrofile Nickel Plated E-SP 5 Pin Double Cylinder - Grand Master Keyed	Satin Nickel	1	Each
	DDS-SS-017	dormakaba Floor Mounted Door Stop	Stainless Steel	1	Each

# HARDWARE PER SET

PROJECT NAME: SANSA - Matjiesfontein


REPORT DATE: 31/01/2025

PROFESSIONAL: SVA Architects

REVISION DATE: 31/01/2025

CONSULTANT: Chantelle Pieters - 066 474 1884 - chantelle.pieters@ahhza.com

REVISION: v 3

Hardware for Set:		T02			
Hardware Set Quantity :		1			
Notes					
Doors (1)		43A.D10			
Product Image	Product Code	Description	Finish	Qty	Units
	DBB-SS-009	dormakaba 102x75x3mm, EN1935 Grade 13, Two ball bearing butt hinge. Fire rated. 120kg Carrying capacity per pair. Finish: Stainless Steel	Stainless Steel	1.5	Pair
	TS91B - SL	dormakaba EN 3 Cam action door closer with standard NON HOLD OPEN slide channel arm. EN1154, certified to ISO 9001. Hydraulic speed control. Standard pull-side door leaf fixing. Transom push-side fixing. EN3 suitable for door width 850-950mm. Fire rated: CERTI FIRE approved (CF 119) for door types ITT 120, MM/IMM 240. (Hold open not recommended for use on fire rated doors)	Silver	1	Each
	DPP-304-BL-SF 150X300	dormakaba 150x300x1.2mm thick Grade 304 stainless steel plate. Stainless Steel Plate to have 6 countersunk holes for screw fixing. (Special Order)	304 Brushed Stainless Steel	1	Each
	DHP-304-BL-SF 150X300	dormakaba DPH301C Pull Handle BT fixed on a 150x300x1.2mm thick Grade 304 stainless steel plate with no cylinder cutout. Stainless Steel Plate to have 6 countersunk holes for screw fixing. (Special Order)	304 Brushed Stainless Steel	1	Each
	Fixing Screws	dormakaba M4 Patent Male / Female fixing screw pack (2 pairs per pack)	Stainless Steel	2	Pack
	DDS-SS-017	dormakaba Floor Mounted Door Stop	Stainless Steel	1	Each
	DSS-131 F	dormakaba 150x150mm FEMALE sign	Stainless Steel	1	Each

# HARDWARE PER SET

PROJECT NAME: SANSA - Matjiesfontein



REPORT DATE: 31/01/2025

PROFESSIONAL: SVA Architects

REVISION DATE: 31/01/2025

CONSULTANT: Chantelle Pieters - 066 474 1884 - chantelle.pieters@ahhza.com

REVISION: v 3

Hardware for Set:		T03			
Hardware Set Quantity :		1			
Notes					
Doors (1)		45A.D10			
Product Image	Product Code	Description	Finish	Qty	Units
	DBB-SS-009	dormakaba 102x75x3mm, EN1935 Grade 13, Two ball bearing butt hinge. Fire rated. 120kg Carrying capacity per pair. Finish: Stainless Steel	Stainless Steel	1.5	Pair
	TS90 - SL	dormakaba EN 3/4 Cam action door closer with standard NON HOLD OPEN slide channel arm. EN1154, certified to ISO 9001. Hydraulic speed control and backcheck. Standard pull side fixing, transom push-side fixing. EN3 suitable for door width 850-950mm, EN4 suitable for door width 950-1100mm. Fire rated: CERTI FIRE approved (CF 119) for door types ITT 120, MM/IMM 240. (Not certified on push face)	Silver	1	Each
	DHP-304-BL-SF 150X300	dormakaba DPH301C Pull Handle BT fixed on a 150x300x1.2mm thick Grade 304 stainless steel plate with no cylinder cutout. Stainless Steel Plate to have 6 countersunk holes for screw fixing. (Special Order)	304 Brushed Stainless Steel	1	Each
	DPP-304-BL-SF 150X300	dormakaba 150x300x1.2mm thick Grade 304 stainless steel plate. Stainless Steel Plate to have 6 countersunk holes for screw fixing. (Special Order)	304 Brushed Stainless Steel	1	Each
	Fixing Screws	dormakaba M4 Patent Male / Female fixing screw pack (2 pairs per pack)	Stainless Steel	2	Pack
	DDS-SS-017	dormakaba Floor Mounted Door Stop	Stainless Steel	1	Each
	DSS-130 M	dormakaba 150x150mm MALE sign	Stainless Steel	1	Each

# HARDWARE PER SET

PROJECT NAME: SANSA - Matjiesfontein

REPORT DATE: 31/01/2025

PROFESSIONAL: SVA Architects

REVISION DATE: 31/01/2025

CONSULTANT: Chantelle Pieters - 066 474 1884 - chantelle.pieters@ahhza.com

REVISION: v 3

HARDWARE FOR SET:		T04			
Hardware Set Quantity :		1			
Notes					
Doors (13)		44A.D17, 45A.D17, 46A.D17, 47A.D17, 48A.D17, 49A.D17, 50A.D17, 2B.D1, 3B.D1, 4B.D1, 5B.D1, 4C.D1, 5C.D1			
Product Image	Product Code	Description	Finish	Qty	Units
	DBB-SS-009	dormakaba 102x75x3mm, EN1935 Grade 13, Two ball bearing butt hinge. Fire rated. 120kg Carrying capacity per pair. Finish: Stainless Steel	Stainless Steel	1.5	Pair
	TH125 WC S.S	dormakaba Lever handle on rose with Bathroom/WC Furniture	Stainless Steel	1	Set
	D035S SS	dormakaba Bathroom Sash Lock. Case dimensions (mm) 102H x 78D. Forend dimensions (mm) 155H x 22W. Backset 57mm. Centres 57mm.	Stainless Steel	1	Each
	DHC-SS-031B	dormakaba Hat and Coat Hook with rubber buffer	Stainless Steel	1	Each

# HARDWARE PER SET

PROJECT NAME: SANSA - Matjiesfontein

REPORT DATE: 31/01/2025

PROFESSIONAL: SVA Architects

REVISION DATE: 31/01/2025

CONSULTANT: Chantelle Pieters - 066 474 1884 - chantelle.pieters@ahhza.com

REVISION: v 3

HARDWARE FOR SET:		T05			
Hardware Set Quantity :		1			
Notes					
Doors (1)		7C.D18			
Product Image	Product Code	Description	Finish	Qty	Units
	DBB-SS-009	dormakaba 102x75x3mm, EN1935 Grade 13, Two ball bearing butt hinge. Fire rated. 120kg Carrying capacity per pair. Finish: Stainless Steel	Stainless Steel	1.5	Pair
	TH125 WC S.S	dormakaba Lever handle on rose with Bathroom/WC Furniture	Stainless Steel	1	Set
	D035S SS	dormakaba Bathroom Sash Lock. Case dimensions (mm) 102H x 78D. Forend dimensions (mm) 155H x 22W. Backset 57mm. Centres 57mm.	Stainless Steel	1	Each
	DDS-SS-017	dormakaba Floor Mounted Door Stop	Stainless Steel	1	Each
	DSS-139 S	dormakaba 150x150mm SHOWER sign	Stainless Steel	1	Each

# HARDWARE PER SET

PROJECT NAME: SANSA - Matjiesfontein

REPORT DATE: 31/01/2025

PROFESSIONAL: SVA Architects

REVISION DATE: 31/01/2025

CONSULTANT: Chantelle Pieters - 066 474 1884 - chantelle.pieters@ahhza.com

REVISION: v 3

HARDWARE FOR SET:		T06			
Hardware Set Quantity :		1			
Notes					
Doors (3)		51A.D2, 1B.D18, 6C.D2			
Product Image	Product Code	Description	Finish	Qty	Units
	DBB-SS-009	dormakaba 102x75x3mm, EN1935 Grade 13, Two ball bearing butt hinge. Fire rated. 120kg Carrying capacity per pair. Finish: Stainless Steel	Stainless Steel	1	Pair
	TS73V DC PA - SL	dormakaba EN 1-4 Rack and pinion door closer with standard NON HOLD OPEN scissor arm and parallel arm bracket. EN1154, certified to ISO 9001. Hydraulic speed control, backcheck and DELAYED ACTION. Standard push side fixing. EN 1 suitable for door width <850mm, EN2 suitable for door width 750-850mm, EN3 suitable for door width 850-950mm, EN4 suitable for door width 950-1100mm. Fire rated. Approved to AS1905 Part 1.	Silver	1	Set
	DPH301B	dormakaba 325x25mm Straight Tubular Pull Handle Flange Fixing  NOTE: external pull handle fitted horizontally. Internal pull handle fitted vertically	Stainless Steel	2	Each
	D032D SS	dormakaba Bathroom Deadlock. Case dimensions (mm) 102H x 78D. Forend dimensions (mm) 155H x 22W. Backset 57mm.	Stainless Steel	1	Each
	DWC-006	dormakaba Disabled WC indicator (Red & White) and turnknob for physically impaired	Stainless Steel	1	Set
	DDS-SS-017	dormakaba Floor Mounted Door Stop	Stainless Steel	1	Each
	DKP-304-SF 600	dormakaba 600x(width of door)x1.2mm thick Grade 304 stainless steel kick plate. Stainless Steel Kick Plate to have 18 countersunk holes for screw fixing. (Special Order)	304 Brushed Stainless Steel	2	Each
	DSS-133 P	dormakaba 150x150mm DISABLED PERSONS sign	Stainless Steel	1	Each

# HARDWARE PER SET

PROJECT NAME: SANSA - Matjiesfontein

REPORT DATE: 31/01/2025

PROFESSIONAL: SVA Architects

REVISION DATE: 31/01/2025

CONSULTANT: Chantelle Pieters - 066 474 1884 - chantelle.pieters@ahhza.com

REVISION: v 3

Hardware for Set:		T07			
Hardware Set Quantity :		1			
Notes					
Doors (10)		4A.D5, 9A.D7, 10A.D14, 11A.D7, 12A.D4, 14A.D11, 15A.D5, 17A.D3, 9C.D11, 10C.D11			
Product Image	Product Code	Description	Finish	Qty	Units
	DBB-SS-009	dormakaba 102x75x3mm, EN1935 Grade 13, Two ball bearing butt hinge. Fire rated. 120kg Carrying capacity per pair. Finish: Stainless Steel	Stainless Steel	3	Pair
	ACBSS	Access control by security specialist		1	Each
	TS91B G-SR	dormakaba NON HOLD OPEN Co-ordinated door closer system for rebated doors between 1350-1900mm. Closing Force EN 3. Hydraulic speed control. Max door width 950mm per leaf. Pull-side fixing. Door closer compliant with EN 1154. Door co-ordinators tested to EN 1158. Door closer is CERTI FIRE approved (Certificate No. CF 119) for door types ITT 120, MM/IMM 240. Certified manufacturer to ISO 9001.	Silver	1	Set
	DPH210 BTB	dormakaba 300x30mm Straight Tubular Pull Handle BTB (BTB Fixing Sets included)	Stainless Steel	2	Pair
	EMC 600 AM	dormakaba Single electromagnetic lock with 600 lbf (2669 N) holding force, mortise-mounted, with lock status sensor (19860502)	Anodized Aluminium	2	Set
	L+Z Bracket 600	dormakaba L+Z Bracket for EMC 600 ALH	Satin Nickel	2	Set
	DDS-SS-017	dormakaba Floor Mounted Door Stop	Stainless Steel	2	Each

# HARDWARE PER SET

PROJECT NAME: SANSA - Matjiesfontein

REPORT DATE: 31/01/2025

PROFESSIONAL: SVA Architects

REVISION DATE: 31/01/2025

CONSULTANT: Chantelle Pieters - 066 474 1884 - chantelle.pieters@ahhza.com

REVISION: v 3

Hardware for Set:		T08			
Hardware Set Quantity :		1			
Notes					
Doors (7)		3A.D9, 5A.D9, 13A.D15, 16A.D15, 20A.D6, 6B.D8, 12C.D16			
Product Image	Product Code	Description	Finish	Qty	Units
	DBB-SS-009	dormakaba 102x75x3mm, EN1935 Grade 13, Two ball bearing butt hinge. Fire rated. 120kg Carrying capacity per pair. Finish: Stainless Steel	Stainless Steel	1.5	Pair
	TS91B - SL	dormakaba EN 3 Cam action door closer with standard NON HOLD OPEN slide channel arm. EN1154, certified to ISO 9001. Hydraulic speed control. Standard pull-side door leaf fixing. Transom push-side fixing. EN3 suitable for door width 850-950mm. Fire rated: CERTI FIRE approved (CF 119) for door types ITT 120, MM/IMM 240. (Hold open not recommended for use on fire rated doors)	Silver	1	Each
	ACBSS	Access control by security specialist		1	Each
	DPH210 BTB	dormakaba 300x30mm Straight Tubular Pull Handle BTB (BTB Fixing Sets included)	Stainless Steel	1	Pair
	EMC 600 AM	dormakaba Single electromagnetic lock with 600 lbf (2669 N) holding force, mortise-mounted, with lock status sensor (19860502)	Anodized Aluminium	1	Set
	L+Z Bracket 600	dormakaba L+Z Bracket for EMC 600 ALH	Satin Nickel	1	Set
	DDS-SS-017	dormakaba Floor Mounted Door Stop	Stainless Steel	1	Each

# HARDWARE PER SET

PROJECT NAME: SANSA - Matjiesfontein

REPORT DATE: 31/01/2025

PROFESSIONAL: SVA Architects

REVISION DATE: 31/01/2025

CONSULTANT: Chantelle Pieters - 066 474 1884 - chantelle.pieters@ahhza.com

REVISION: v 3

Hardware for Set:		T09			
Hardware Set Quantity :		1			
Notes					
Doors (4)		27A.D1, 40A.D16, 11B.D16, 13C.D16			
Product Image	Product Code	Description	Finish	Qty	Units
	DBB-SS-009	dormakaba 102x75x3mm, EN1935 Grade 13, Two ball bearing butt hinge. Fire rated. 120kg Carrying capacity per pair. Finish: Stainless Steel	Stainless Steel	1.5	Pair
	TS91B - SL	dormakaba EN 3 Cam action door closer with standard NON HOLD OPEN slide channel arm. EN1154, certified to ISO 9001. Hydraulic speed control. Standard pull-side door leaf fixing. Transom push-side fixing. EN3 suitable for door width 850-950mm. Fire rated: CERTI FIRE approved (CF 119) for door types ITT 120, MM/IMM 240. (Hold open not recommended for use on fire rated doors)	Silver	1	Each
	DPH210 BTB	dormakaba 300x30mm Straight Tubular Pull Handle BTB (BTB Fixing Sets included)	Stainless Steel	1	Pair
	D037D SS	dormakaba Cylinder Deadlock. Case dimensions (mm) 116.5H x 78D. Forend dimensions (mm) 168H x 22W. Backset 57mm.	Stainless Steel	1	Each
	DDC206301 GMK	dormakaba 63mm - 31.5+31.5mm Europrofile Nickel Plated E-SP 5 Pin Double Cylinder - Grand Master Keyed	Satin Nickel	1	Each
	DCE-002 S.S	dormakaba Round Cylinder escutcheon	Stainless Steel	1	Pair
	DDS-SS-017	dormakaba Floor Mounted Door Stop	Stainless Steel	1	Each

# HARDWARE PER SET

PROJECT NAME: SANSA - Matjiesfontein

REPORT DATE: 31/01/2025

PROFESSIONAL: SVA Architects

REVISION DATE: 31/01/2025

CONSULTANT: Chantelle Pieters - 066 474 1884 - chantelle.pieters@ahhza.com

REVISION: v 3

Hardware for Set:		T10			
Hardware Set Quantity :		1			
Notes					
Doors (1)		54A.D8			
Product Image	Product Code	Description	Finish	Qty	Units
	DBB-SS-009	dormakaba 102x75x3mm, EN1935 Grade 13, Two ball bearing butt hinge. Fire rated. 120kg Carrying capacity per pair. Finish: Stainless Steel	Stainless Steel	1.5	Pair
	TS92G - AB - SL	dormakaba EN 1-4 Cam action door closer with NON HOLD OPEN slide channel arm and angle bracket. EN1154, certified to ISO 9001. Adjustable hydraulic speed control. Standard push-side door leaf fixing. Transom push-side fixing. EN1 suitable for door width < 750mm, EN2 suitable for door width 750-850mm, EN3 suitable for door width 850-950mm, EN4 suitable for door width 950-1100mm. Fire rated: CERTI FIRE approved (CF 119) for door types ITT 120, MM/IMM 240	Silver	1	Set
	DSC204101 GMK	dormakaba 40.5 - Europrofile Nickel Plated E-SP 5 Pin Single Cylinder - Grand Master Keyed	Satin Nickel	1	Each
	PHA2 S SD	dormakaba Two point locking panic bar - Single door - Door leaf 1000mm wide x 2270mm high (2201. 2104. PHX02. PHX04)	-	1	Set
	PHT3901	dormakaba Exterior access lock with lever handle (Cylinder not included)	Satin Nickel	1	Each

# HARDWARE PER SET

PROJECT NAME: SANSA - Matjiesfontein



REPORT DATE: 31/01/2025

PROFESSIONAL: SVA Architects

REVISION DATE: 31/01/2025

CONSULTANT: Chantelle Pieters - 066 474 1884 - chantelle.pieters@ahhza.com

REVISION: v 3

Hardware for Set:		T11			
Hardware Set Quantity :		1			
Notes					
Doors (2)		25A.D1, 26A.D1			
Product Image	Product Code	Description	Finish	Qty	Units
	DBB-SS-009	dormakaba 102x75x3mm, EN1935 Grade 13, Two ball bearing butt hinge. Fire rated. 120kg Carrying capacity per pair. Finish: Stainless Steel	Stainless Steel	1.5	Pair
	TS91B - SL	dormakaba EN 3 Cam action door closer with standard NON HOLD OPEN slide channel arm. EN1154, certified to ISO 9001. Hydraulic speed control. Standard pull-side door leaf fixing. Transom push-side fixing. EN3 suitable for door width 850-950mm. Fire rated: CERTI FIRE approved (CF 119) for door types ITT 120, MM/IMM 240. (Hold open not recommended for use on fire rated doors)	Silver	1	Each
	DHP-304-BL-SF 150X300	dormakaba DPH301C Pull Handle BT fixed on a 150x300x1.2mm thick Grade 304 stainless steel plate with no cylinder cutout. Stainless Steel Plate to have 6 countersunk holes for screw fixing. (Special Order)	304 Brushed Stainless Steel	1	Each
	DPP-304-BL-SF 150X300	dormakaba 150x300x1.2mm thick Grade 304 stainless steel plate. Stainless Steel Plate to have 6 countersunk holes for screw fixing. (Special Order)	304 Brushed Stainless Steel	1	Each
	Fixing Screws	dormakaba M4 Patent Male / Female fixing screw pack (2 pairs per pack)	Stainless Steel	2	Pack
	D032D SS	dormakaba Bathroom Deadlock. Case dimensions (mm) 102H x 78D. Forend dimensions (mm) 155H x 22W. Backset 57mm.	Stainless Steel	1	Each
	DWC-005	dormakaba Bathroom WC indicator (Red and White) and turnknob	Stainless Steel	1	Set
	DDS-SS-017	dormakaba Floor Mounted Door Stop	Stainless Steel	1	Each
	DSS-132 MF	dormakaba 150x150mm MALE/FEMALE sign	Stainless Steel	1	Each

# HARDWARE PER SET

PROJECT NAME: SANSA - Matjiesfontein

REPORT DATE: 31/01/2025

PROFESSIONAL: SVA Architects

REVISION DATE: 31/01/2025

CONSULTANT: Chantelle Pieters - 066 474 1884 - chantelle.pieters@ahhza.com

REVISION: v 3

Hardware for Set:		T12			
Hardware Set Quantity :		1			
Notes					
Doors (1)		52A.D12			
Product Image	Product Code	Description	Finish	Qty	Units
	DBB-SS-009	dormakaba 102x75x3mm, EN1935 Grade 13, Two ball bearing butt hinge. Fire rated. 120kg Carrying capacity per pair. Finish: Stainless Steel	Stainless Steel	3	Pair
	TS91B G-SR	dormakaba NON HOLD OPEN Co-ordinated door closer system for rebated doors between 1350-1900mm. Closing Force EN 3. Hydraulic speed control. Max door width 950mm per leaf. Pull-side fixing. Door closer compliant with EN 1154. Door co-ordinators tested to EN 1158. Door closer is CERTI FIRE approved (Certificate No. CF 119) for door types ITT 120, MM/IMM 240. Certified manufacturer to ISO 9001.	Silver	1	Set
	DSC204101 GMK	dormakaba 40.5 - Europrofile Nickel Plated E-SP 5 Pin Single Cylinder - Grand Master Keyed	Satin Nickel	1	Each
	PHA3 S DD	dormakaba Three point locking panic bar - Double door - Door leaf 1000mm wide x 2270mm high (2101. 2104. 2104. 2201. PHX02. PHX04)	Stainless Steel, -	1	Set
	PHT3901	dormakaba Exterior access lock with lever handle (Cylinder not included)	Satin Nickel	1	Each
	DDS-SS-017	dormakaba Floor Mounted Door Stop	Stainless Steel	2	Each

PROJECT NAME: SANSA - Matjiesfontein


REPORT DATE: 31/01/2025

PROFESSIONAL: SVA Architects

REVISION DATE: 31/01/2025

CONSULTANT: Chantelle Pieters - 066 474 1884 - chantelle.pieters@ahhza.com

REVISION: v 3

Product Image	Product Code	Description	Finish	Units	Qty	Price (ZAR)	Total (ZAR)
	DBB-SS-009	dormakaba dormakaba dormakaba dormakaba 102x75x3mm, EN1935 Grade 13, Two ball bearing butt hinge. Fire rated. 120kg Carrying capacity per pair. Finish: Stainless Steel	Stainless Steel	Pair	93.0		
	ACBSS	Access control by security specialist		Each	17.0		
	TS73V DC PA-SL	dormakaba dormakaba dormakaba dormakaba EN 1-4 Rack and pinion door closer with standard NON HOLD OPEN scissor arm and parallel arm bracket. EN1154, certified to ISO 9001. Hydraulic speed control, backcheck and DELAYED ACTION. Standard push side fixing. EN 1 suitable for door width <850mm, EN2 suitable for door width 750-850mm, EN3 suitable for door width 850-950mm, EN4 suitable for door width 950-1100mm. Fire rated. Approved to AS1905 Part 1.	Silver	Set	3.0		
	TS90-SL	dormakaba dormakaba dormakaba dormakaba EN 3/4 Cam action door closer with standard NON HOLD OPEN slide channel arm. EN1154, certified to ISO 9001. Hydraulic speed control and backcheck. Standard pull side fixing, transom push-side fixing. EN3 suitable for door width 850-950mm, EN4 suitable for door width 950-1100mm. Fire rated: CERTI FIRE approved (CF 119) for door types ITT 120, MM/IMM 240. (Not certified on push face)	Silver	Each	1.0		
	TS91B-SL	dormakaba dormakaba dormakaba dormakaba EN 3 Cam action door closer with standard NON HOLD OPEN slide channel arm. EN1154, certified to ISO 9001. Hydraulic speed control. Standard pull-side door leaf fixing. Transom push-side fixing. EN3 suitable for door width 850-950mm. Fire rated: CERTI FIRE approved (CF 119) for door types ITT 120, MM/IMM 240. (Hold open not recommended for use on fire rated doors)	Silver	Each	14.0		
	TS91B G-SR	dormakaba dormakaba dormakaba dormakaba NON HOLD OPEN Co-ordinated door closer system for rebated doors between 1350-1900mm. Closing Force EN 3. Hydraulic speed control. Max door width 950mm per leaf. Pull-side fixing. Door closer compliant with EN 1154. Door co-ordinators tested to EN 1158. Door closer is CERTI FIRE approved (Certificate No. CF 119) for door types ITT 120, MM/IMM 240. Certified manufacturer to ISO 9001.	Silver	Set	11.0		
	TS92G-AB-SL	dormakaba dormakaba dormakaba dormakaba EN 1-4 Cam action door closer with NON HOLD OPEN slide channel arm and angle bracket. EN1154, certified to ISO 9001. Adjustable hydraulic speed control. Standard push-side door leaf fixing. Transom push-side fixing. EN1 suitable for door width < 750mm, EN2 suitable for door width 750-850mm, EN3 suitable for door width 850-950mm, EN4 suitable for door width 950-1100mm. Fire rated: CERTI FIRE approved (CF 119) for door types ITT 120, MM/IMM 240	Silver	Set	1.0		
	DHP-304-BL-SF 150X300	dormakaba dormakaba dormakaba dormakaba DPH301C Pull Handle BT fixed on a 150x300x1.2mm thick Grade 304 stainless steel plate with no cylinder cutout. Stainless Steel Plate to have 6 countersunk holes for screw fixing. (Special Order)	304 Brushed Stainless Steel	Each	4.0		
	DPH210 BTB	dormakaba dormakaba dormakaba dormakaba 300x30mm Straight Tubular Pull Handle BTB (BTB Fixing Sets included)	Stainless Steel	Pair	31.0		
	DPH301B	dormakaba dormakaba dormakaba dormakaba 325x25mm Straight Tubular Pull Handle Flange Fixing	Stainless Steel	Each	6.0		

# BILL OF MATERIALS

PROJECT NAME: SANSA - Matjiesfontein

REPORT DATE: 31/01/2025

PROFESSIONAL: SVA Architects

REVISION DATE: 31/01/2025

CONSULTANT: Chantelle Pieters - 066 474 1884 - chantelle.pieters@ahhza.com

REVISION: v 3

Product Image	Product Code	Description	Finish	Units	Qty	Price (ZAR)	Total (ZAR)
	DPP-304-BL-SF 150X300	dormakaba dormakaba dormakaba dormakaba 150x300x1.2mm thick Grade 304 stainless steel plate. Stainless Steel Plate to have 6 countersunk holes for screw fixing. (Special Order)	304 Brushed Stainless Steel	Each	4.0		
	Fixing Screws	dormakaba dormakaba dormakaba dormakaba M4 Patent Male / Female fixing screw pack (2 pairs per pack)	Stainless Steel	Pack	8.0		
	TH125 Cyl S.S	dormakaba dormakaba dormakaba dormakaba Lever handle on rose with Cylinder escutcheons	Stainless Steel	Set	8.0		
	TH125 WC S.S	dormakaba dormakaba dormakaba dormakaba Lever handle on rose with Bathroom/WC Furniture	Stainless Steel	Set	14.0		
	D032D SS	dormakaba dormakaba dormakaba dormakaba Bathroom Deadlock. Case dimensions (mm) 102H x 78D. Forend dimensions (mm) 155H x 22W. Backset 57mm.	Stainless Steel	Each	5.0		
	D035S SS	dormakaba dormakaba dormakaba dormakaba Bathroom Sash Lock. Case dimensions (mm) 102H x 78D. Forend dimensions (mm) 155H x 22W. Backset 57mm. Centres 57mm.	Stainless Steel	Each	14.0		
	D036S SS	dormakaba dormakaba dormakaba dormakaba Cylinder Sash Lock. Case dimensions (mm) 116.5H x 78D. Forend dimensions (mm) 168H x 22W. Backset 57mm. Centres 61mm.	Stainless Steel	Each	8.0		
	D037D SS	dormakaba dormakaba dormakaba dormakaba Cylinder Deadlock. Case dimensions (mm) 116.5H x 78D. Forend dimensions (mm) 168H x 22W. Backset 57mm.	Stainless Steel	Each	4.0		
	EMC 600 AM	dormakaba dormakaba dormakaba dormakaba Single electromagnetic lock with 600 lbf (2669 N) holding force, mortise-mounted, with lock status sensor (19860502)	Anodized Aluminium	Set	27.0		
	L+Z Bracket 600	dormakaba dormakaba dormakaba dormakaba L+Z Bracket for EMC 600 ALH	Satin Nickel	Set	27.0		
	DDC206301 GMK	dormakaba dormakaba dormakaba dormakaba 63mm - 31.5+31.5mm Europrofile Nickel Plated E-SP 5 Pin Double Cylinder - Grand Master Keyed	Satin Nickel	Each	12.0		
	DSC204101 GMK	dormakaba dormakaba dormakaba dormakaba 40.5 - Europrofile Nickel Plated E-SP 5 Pin Single Cylinder - Grand Master Keyed	Satin Nickel	Each	2.0		

# BILL OF MATERIALS

PROJECT NAME: SANSA - Matjiesfontein

REPORT DATE: 31/01/2025

PROFESSIONAL: SVA Architects

REVISION DATE: 31/01/2025

CONSULTANT: Chantelle Pieters - 066 474 1884 - chantelle.pieters@ahhza.com

REVISION: v 3

Product Image	Product Code	Description	Finish	Units	Qty	Price (ZAR)	Total (ZAR)
	DCE-002 S.S	dormakaba dormakaba dormakaba dormakaba Round Cylinder escutcheon	Stainless Steel	Pair	4.0		
	DWC-005	dormakaba dormakaba dormakaba dormakaba Bathroom WC indicator (Red and White) and turnknob	Stainless Steel	Set	2.0		
	DWC-006	dormakaba dormakaba dormakaba dormakaba Disabled WC indicator (Red & White) and turnknob for physically impaired	Stainless Steel	Set	3.0		
	PHA2 S SD	dormakaba dormakaba dormakaba dormakaba Two point locking panic bar - Single door - Door leaf 1000mm wide x 2270mm high (2201. 2104. PHX02. PHX04)	-	Set	1.0		
	PHA3 S DD	dormakaba dormakaba dormakaba dormakaba Three point locking panic bar - Double door - Door leaf 1000mm wide x 2270mm high (2101. 2104. 2104. 2201. PHX02. PHX04)	Stainless Steel, -	Set	1.0		
	PHT3901	dormakaba dormakaba dormakaba dormakaba Exterior access lock with lever handle (Cylinder not included)	Satin Nickel	Each	2.0		
	DDS-SS-017	dormakaba dormakaba dormakaba dormakaba Floor Mounted Door Stop	Stainless Steel	Each	49.0		
	DHC-SS-031B	dormakaba dormakaba dormakaba dormakaba Hat and Coat Hook with rubber buffer	Stainless Steel	Each	13.0		
	DKP-304-SF 600	dormakaba dormakaba dormakaba dormakaba 600x(width of door)x1.2mm thick Grade 304 stainless steel kick plate. Stainless Steel Kick Plate to have 18 countersunk holes for screw fixing. (Special Order)	304 Brushed Stainless Steel	Each	6.0		
	DSS-130 M	dormakaba dormakaba dormakaba dormakaba 150x150mm MALE sign	Stainless Steel	Each	1.0		
	DSS-131 F	dormakaba dormakaba dormakaba dormakaba 150x150mm FEMALE sign	Stainless Steel	Each	1.0		
	DSS-132 MF	dormakaba dormakaba dormakaba dormakaba 150x150mm MALE/FEMALE sign	Stainless Steel	Each	2.0		

# BILL OF MATERIALS

PROJECT NAME: SANSA - Matjiesfontein

REPORT DATE: 31/01/2025

PROFESSIONAL: SVA Architects

REVISION DATE: 31/01/2025

CONSULTANT: Chantelle Pieters - 066 474 1884 - chantelle.pieters@ahhza.com

REVISION: v 3

Product Image	Product Code	Description	Finish	Units	Qty	Price (ZAR)	Total (ZAR)
	DSS-133 P	dormakaba dormakaba dormakaba dormakaba 150x150mm DISABLED PERSONS sign	Stainless Steel	Each	3.0		
	DSS-139 S	dormakaba dormakaba dormakaba dormakaba 150x150mm SHOWER sign	Stainless Steel	Each	1.0		
<b>Total (ZAR)</b>							

**ALL PRODUCTS, PRODUCT SPECIFICATIONS, PRICES AND DATA SHEETS ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE.**

dormakaba South Africa Pty Ltd, and its employees, and all persons acting on its or their behalf, disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any specification document or in any other disclosure relating to any product.

dormakaba South Africa Pty Ltd makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product.

To the maximum extent permitted by applicable law, dormakaba South Africa Pty Ltd disclaims

- i. any and all liability arising out of the application or use of any product,
- ii. any and all liability, including without limitation special, consequential or incidental damages, and
- iii. any and all implied warranties, including warranties of fitness for particular purpose, non infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on dormakaba South Africa Pty Ltd knowledge of typical requirements that are often placed on dormakaba products in generic applications.

Such statements are not binding statements about the suitability of products for a particular application.

It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application.

Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts.

Product specifications do not expand or otherwise modify dormakaba South Africa Pty Ltd terms and conditions of purchase, including but not limited to the warranty expressed therein.

Customers using or selling dormakaba products not expressly indicated for use in such applications do so at their own risk.

Please contact authorized dormakaba personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of dormakaba South Africa Pty Ltd.

Product names and markings noted herein may be trademarks of their respective owners.