



Type Mark	Count	Description	Frame Finish	Door Leaf Finish	Ironmongery Type
D8	1	D8 - Varikust (VKF105) Solid timber, single door with steel frame to receive painted finish. Size and configuration as shown on the Project Door Schedule. SANS 545 classification: Performance: Heavy duty. Exposure: External. Fire rating: Non-rated. Acoustic rating: Rw 48dB. Configuration: Single Leaf, single swing. Doors to be delivered with protection for the finished surfaces. FRAME: To Manufacturer's details. Size: As shown on the Contract Drawings and the Project Door Schedule. LEAF: Solid timber, flush panel, single door. External face to receive painted finish, internal face to receive 0.7mm Rovere Valdweg Alevé woodgrain laminate. Thickness: As per manufacturer. Ironmongery: To receive suitable ironmongery for fire escape doors.	Primed and painted to match RAL 7043	Primed and painted as per paint schedule on one side, and Rovere Valdweg Alevé woodgrain laminate on the internal face.	Refer to ironmongery schedule

GENERAL NOTES		Rev	Date	Int	Description
- All installation procedures to comply with good building practice and deemed to satisfy the Architect's requirements. -All exposed timber to be rubbed down smooth prior the application of any finish. -To be supplied and installed with all door frames. -This drawing to be read in conjunction with GA-layouts and all dimensions to be checked on site. -Refer any discrepancies to the Architect in writing.		A	2024-11-11		For Tender
		B	2024-11-25		For Tender

Title.	Drawing No.	Scale	Date	Rev.
Door Type D8	SMFN-SVA-AR-SH-30_1008	1 : 25	2020/09/02	B