



Door to have floor springs, refer to Door details

Type Mark	Count	Description	Frame Finish	Door Leaf Finish	Ironmongery Type
D12	1	D12- Rovere Valdweg Aleve woodgrain laminate faced, solid timber, sound stop dbl door with light oak edgings all round and Light Oak frame to receive oil finish. Size and configuration: As shown on the Project Door Schedule. Fire rating: Non-rated. Doors to be labelled, indicating manufacturers name, reference no. and year of manufacture. Acoustic rating: Rw 45 dB. FRAME: 44x69mm solid Light Oak frame to receive oil finish with 45x15mm rebates per detail drawings. With custom architrave per detail drawings. LEAF: Solid timber, flush panel, sound stop double door with Light Oak edgings all round. Facing: 0.7mm Rovere Valdweg Aleve woodgrain laminate to clad all faces and edges of door leaf. Edges: 25mm Concealed light oak edge. Thickness: 44mm. Door to have floor springs as per Door Details.	Jax-Oleum oil finish - Corn Silk	Rovere Valdweg Aleve woodgrain laminate	

GENERAL NOTES		Rev	Date	Int	Description
- All installation procedures to comply with good building practice and deemed to satisfy the Architect's requirements. - All exposed timber to be rubbed down smooth prior the application of any finish. - To be supplied and installed with all door frames. - This drawing to be read in conjunction with GA-layouts and all dimensions to be checked on site. - Refer any discrepancies to the Architect in writing.		A	2024-11-11		For Tender
		B	2024-11-25		For Tender

Title.	Drawing No.	Scale	Date	Rev.
<b>Door Type D12</b>	<b>SMFN-SVA-AR-30_1012</b>	1 : 25	2020/09/02	B