

# GIZA EYELID

## MODEL NUMBER

## GIZA EYELID

## SPECIFICATIONS

**HOUSING** : LM 6 die cast aluminium.

**LIGHT SOURCE** : The fitting is designed to operate a range of LED's up to 13W.

**DIFFUSER** : UV stabilised high impact opal acrylic.

**FINISH** : Powder coated.

**MOUNTING** : Wall mounted.

**CONTROL GEAR** : The electronic supply is suitable for operation with 220 – 240 volts, 50 hertz single phase.

**FASTENERS** : All external screws are stainless steel. Tamper proof screws available on request.

**GASKET** : Silicone sponge gasket. Silicone gaskets perform in a wide temperature range -40° C to +200° C.

**INGRESS PROTECTION** : IP 65.

**OPERATING TEMPERATURE** : (Ta) ≤ 35° C.

**WEIGHT** : 2.7 Kg total including control gear.

**FEATURES** : Emergency gear available on request.




## LIGHT SOURCE

### LED ZHAGA BOARDS


LED CURRENT (mA)	LUMINAIRE WATTAGE (W)	COLOUR TEMP (K)	NOMINAL FLUX (lm)
700mA	13W	4000K	2131 lm
		3000K	2021 lm

## APPLICATION AREAS

Indoor and outdoor application.  
Commercial developments.  
Retail developments.  
Shopping malls.  
Public buildings.  
Residential developments.




## DIMENSIONS IN MM



Side View

Front View




Mounting Plate Detail

## COLOURS

	Black (B)		Matt Silver (M)
	White (W)		Charcoal Grey (C)

## LIGHT DISTRIBUTION

GIZA EYELID 13W



cd/klm  
C0 - C180 C90 - C270

